

AP wired B
AP wired A
AP wired C
AP wired G
AP wired F
Null MAC
Client K
iPhone Client

mesh_data_remotewap_wired.pcapng

DTLS Application Data (23)

Version	DTLS 1.0 (0xfeff)
Epoch	1
Length	64

DTLS Application Data (23)

Version	DTLS 1.0 (0xfeff)
Epoch	1
Length	80

DTLS Application Data (23)

Version	DTLS 1.0 (0xfeff)
Epoch	1
Length	64

DTLS Application Data (23)

Version	DTLS 1.0 (0xfeff)
Epoch	1
Length	80

DTLS Application Data (23)

Version	DTLS 1.0 (0xfeff)
Epoch	1
Length	64

DTLS Application Data (23)

Version	DTLS 1.0 (0xfeff)
Epoch	1
Length	80

DTLS Application Data (23)

Version	DTLS 1.0 (0xfeff)
Epoch	1
Length	64

DTLS Application Data (23)

Version	DTLS 1.0 (0xfeff)
Epoch	1
Length	80

Frame 1 |
2017-02-12T17:21:03.607455Z

Frame 2 |
2017-02-12T17:21:03.607724Z

Frame 5 |
2017-02-12T17:21:04.005089Z

Frame 6 |
2017-02-12T17:21:04.005325Z

Frame 7 |
2017-02-12T17:21:04.026189Z

Frame 8 |
2017-02-12T17:21:04.026223Z

Frame 9 |
2017-02-12T17:21:04.072562Z

Frame 10 |
2017-02-12T17:21:04.072595Z

AP wired B

AP wired A

AP wired C

AP wired G

AP wired F

Null MAC

Client K

iPhone Client

Probe Request (0x0004)

Dst	00:d7:8f:d3:53:d0
Src	00:00:00:00:00:00
Seq	0

Data (0x0020)

Dst	00:56:cd:ee:f1:71
Src	00:23:5d:c9:5a:c7
BSS	00:d7:8f:d3:53:d0
Seq	0
Len	672

Data (0x0020)

Dst	00:23:5d:c9:5a:c7
Src	00:56:cd:ee:f1:71
BSS	00:d7:8f:d3:53:d0
Seq	2304
Len	672

💡 Probe Request – active scanning: client solicits responses from APs; directed (specific SSID) or wildcard (broadcast SSID); faster than passive scanning (beacon-only)

Frame 12 | 2017-02-12T17:21:04.741609Z

Frame 13 | 2017-02-12T17:21:04.771366Z